

Easy viewing and readable scale graduation.



Insulation Tester

Part No. TA453PD

List Price: JPY 19,800



FEATURES

- ◆ Test voltage DC500V/250V/125V
- ◆ Easy viewing and readable scale graduations
- ◆ One-shot or continuous measurement push switch
- ◆ DCV measurement range(DC60V)
- ◆ Auto discharge function
- ◆ Inner battery check range
- ◆ Battery DC9V(006P)

SPECIFICATIONS

	Measuring range	Best accuracy
MΩ	500V/ 100MΩ	1st effective measurement range : ±5% of full scale
(Insulation Resistance)	250V/ 100MΩ	2nd effective measurement range : ±10% of full scale
	125V/ 100MΩ	
DCV	60V	±5% of full scale
ACV	600V	±5% of full scale

Meter type	Internal magnet, Taut-band meter(48μA)
AC rectifier form	Half-wave rectification(Mean value indication rms value converted)
Accuracy assurance temperature / humidity	23±5°C 75%RH or below No condensation
Operating temperature / humidity	0°C~43°C 80%RH or below No condensation
Storage temperature / humidity	-10°C~50°C 70%RH or below No condensation
Operating environment	Altitude 2000m or less, environmental pollution degree II
Power consumption	Approx. 2.6W(At 1000V/2000MΩ range)
Battery consumption	Checked by BATTERY CHECK range
Safety standards	IEC61010-1 CAT.III 600V
IP rate	IP20
Battery	6LR61(9V) x 1
Size / Mass	H144 x W99 x D43mm / 310g
Standard accessories included	Test lead(TL-508Sa), Carrying case(C-08S), Instruction manual



Includes test leads and a carrying case